
BUTTERFLY VALVE CK




Butterfly valve CK with pneumatic actuator.

TECHNICAL DATA

Nominal diameter:	DN 80 - DN 250
Face to face:	EBRO works standard
Top flange:	EN ISO 5211
Tightness check:	EN 12266 (Leakage rate A) ISO 5208, Category 3
Temperature range:	-10°C to +60°C (depending on pressure and media)
Operating pressure:	max. 3 bar
Body:	Aluminium
Disc:	ball contour 3 mm NBR-white coated 90° Shore A (FDA harmless) overdimension to body seat 0,3 mm DN 100 0,35 mm DN 250
Shaft:	AISI 316 (1.4401) alternative upon request

FEATURES


- Wafer pattern butterfly valve with centrically mounted disc
- Body with mutual bond for clamp ring connection
- The inside contour is spherically machined
- Through-going seat without any edges
- Low consumption
- Fast and easy dismantling
- Maintenance-free



GENERAL APPLICATIONS

- Food industry
- Bulk goods

BUTTERFLY VALVE CK



Butterfly valve type CK

DN [mm]	Size [in]	Dimensions [mm]												Weight [kg]
		A	B	C	D	E	F	Flange	G	H1	H2	J	Z	
80	**3**	86	87	173	92	66	65	F05	10	16	30	12	33	0,9
100	**4**	96	97	193	115	68	65	F05	10	16	30	12	66	1,3
120	**5**	109	105	214	135	72	90	F07	12	20	38	16	89	1,9
200	**8**	179	166	345	215	85	90	F07	16	20	38	20	175	5,8
250	**10**	206	189	395	265	85	90	F07	16	20	38	20	230	7,7

Subject to change without notice

EBRO ARMATUREN®

www.ebro-armaturen.com
post@ebro-armaturen.com

10.2012